


RES-EASE® FIXING CLIPS FOR CONCEALED FIXED DECKING

RESIDENTIAL LOW-PITCH ROOFING SYSTEM
SUITABLE FOR SPEED DECK ULTRA® CONCEALED
FIXED DECKING SHEETS ONLY

PRODUCT INSTALLATION SUPPLEMENT



1-2-3




RES-EASE® FIXING CLIPS



RESIDENTIAL FIXING SOLUTION FOR SPEED
DECK ULTRA® CONCEALED FIXED DECKING

BASIC INSTALLATION PROCEDURE:


1. Ensure battens are correctly installed and in-plane.
2. Trim first clips on each row to suit first sheet.
 - a. Full sheet: At groove near upstand.
 - b. Part sheet: Along rail to suit.
3. Add an extra portion to the end of each set of 3 clips to make 4 (or to suit part sheet).




4. Align first clips on battens so that they are parallel and in-line.
5. Screw down clips in order from trailing to leading – **1-2-3**.
6. Make sure there is 1 more upstand than number of ribs plus overlap.
7. Snap on first sheet – **1-2-3**. Ensuring correct overhangs



8. Install another set of clips with 3 upstands and screw down in order – **1-2-3**.



9. Snap on second sheet, 1-2-3.
10. Repeat 8 and 9 until all sheeting is installed.
11. Turn up sheet ends at ridge and turn down sheet ends at eave, using the Speed Deck Ultra® turn up/down tool.
12. Fix edge pans through to battens.
13. Using a 6.2-13 sealed hex head fastener, fasten each pan centrally to top batten, at ridge. If pitch is over 20 degrees, use 2 fasteners evenly spaced.
14. Flash as per standard practice, ensuring flashing at roof edges covers at least the closest full rib of the sheeting.



ALTERNATIVE INSTALLATION METHOD

Another method of installation involves Steps 1, 2 and 4 above, then fixing all clips down on all supports as indicated in Step 5.

Once all clips are installed and screwed down, the sheets can be installed by pushing down each rib on the clip. Snap ribs on to clips in order 1-2-3 as before.

Continue installing sheets until all sheeting is installed. Then Continue from Step 11.


Each clip box has an illustration of both clip fixing techniques. For more information related to installation, refer to the Product Technical Manual. Please visit the Stramit website to download your copy.

FOR BAL LOW OR BAL 12.5:


- Install Speed Deck Ultra® Concealed Fixed Decking End Caps, with silicone sealant, into the ribs at the eaves so that they are directly above the fascia.

IMPORTANT

Do snap ribs onto clips in the correct order **1-2-3**, without excessive force.




Do walk only in Overlap and Central Pans, and Underlap pans that are supported by another sheet.




Do ensure there is an upstand at the underlap

- Underlap must be hooked onto clip
- Fastener as required by type of batten




Do turn-ups and turn-downs after sheet laying



SYSTEM COMPONENTS

SPEED DECK ULTRA® CONCEALED FIXED DECKING



RES-EASE® FIXING CLIP

1 set per sheet per support


Centralised Fastening protects sheets

Modular Design - Less Waste

No sharp steel edges

Universal Ribs

Precision tolerances provide consistent pitch, preventing roof creep during installation






ACCESSORIES

Speed Deck Ultra® Concealed Fixed Decking Rib End Cap

1 per rib at eaves.
For use in BAL LOW or
BAL 12.5 applications



FASTENERS

Clip Fixing (one per upstand)	
Steel battens (0.48mm and 0.55mm BMT)	
	Vortex® 6.2-13x35mm hex-head self-drilling and threading screws with no sealing washer.
Timber battens	
	Vortex® Plus 6.2-13x50mm self-drilling screws.
Pan Fixing	
Timber and Steel battens (0.48mm and 0.55mm BMT)	
	Vortex® Plus 6.2-13x25mm self-drilling screws.

The Stramit webpage can be found at:

www.stramit.com.au

Details of many Stramit products can also be seen on the AIA site 'Product Selector' at:

www.selector.com.au

For product technical support enquiries please contact: techsupport@stramit.com.au

IMPORTANT NOTICE AND DISCLAIMER

The information contained within this brochure is for general use and information only. Before application in a particular situation, you should obtain appropriate independent qualified expert advice confirming the suitability of product(s) and information in question for the application proposed. Except to the extent permitted by law, Stramit excludes all liability (including liability for negligence) for all loss and damage, whether direct or indirect, resulting from the use of the information provided in this brochure.

© 2025 Stramit Corporation Pty Limited ABN 57 005 010 195. A member of the Fletcher Building Group. RES-EASE®, Speed Deck Ultra® and use of ™ and ® indicates trademarks of Stramit Corporation Pty Limited. This document replaces all previous issues. Please destroy, or clearly mark as superseded, all previous issues. STR132_JUNE25.

For more information and ordering, reach out to your Account Manager, today.



Scan to learn more