

# STRAMIT FLAMMABILITY STATEMENT

OCTOBER 2021 | THIS VERSION SUPERCEDES ALL PREVIOUS VERSIONS

## FIRE RESISTANCE

Fire resistance is such an important topic and one that we take seriously here at Stramit. It's important for everyone in our building industry, including product manufacturers, architects, builders, engineers and installers.

### NATIONAL CONSTRUCTION CODE

The National Construction Code (NCC) sets out technical provisions for the design, construction and performance of buildings throughout Australia, which include criteria for the assessment of building elements under fire conditions.

Part C1 of Volume One of the NCC 2019 states the provisions that need to be met for fire resistance and stability when proposing a Deemed to Satisfy solution. As stated in Part C1.9, building elements in certain types of fire resisting construction, for example external or common walls, load bearing internal walls etc, must have all components that are non-combustible. Stramit® wall sheeting used in this type of construction must meet this requirement. Part C1.9(e) gives a list of materials that may be used where non-combustible components are required. One option is metal sheeting with a combustible surface finish less than 1mm in thickness, with a Spread of Flame Index not exceeding 0.

Similarly, in Volume Two of the NCC 2019, Part 3.7 sets out the requirements for Fire Safety, and Part 3.7.1 states the Fire properties for materials and construction. The Acceptable Construction Practice includes a section 3.7.1.1 on General concessions - non-combustible materials. One of the options mentioned here as non-combustible is metal sheeting with a combustible surface finish less than 1mm in thickness, with a Spread of Flame Index not exceeding 0.

### MATERIALS TESTING

Stramit® roofing, cladding, rainwater and structural building products are manufactured from steel produced by Bluescope® Steel or Pacific Coil Coaters (through Selection Steel). Both organisations have had independent tests on their materials carried out by CSIRO or AWTA. The testing was conducted in accordance with the Australian Standard AS1530.3 'Simultaneous Determination of Ignitability, Flame Propagation, Heat Release and Smoke Release.' All materials had a surface finish less than 1mm in thickness and a Spread of Flame Index of 0. More detail is given in the table over the page.

## TECHNICAL SUMMARY

Steel Source	Base Metal Thickness (mm)	Finish	Certificate Number	Ignitability Index (0-20)	Spread of Flame Index (0-10)	Heat Evolved Index (0-10)	Smoke Developed Index (0-10)
Bluescope	0.35	COLORBOND®	FNE11605	0	0	0	2
Bluescope	0.7	COLORBOND® METALLIC	FNE11604	0	0	0	2
Bluescope	0.42	ZINCALUME®	FNE11602	0	0	0	2
Bluescope	0.42	TRUECORE®	FNE11601	0	0	0	1
Bluescope	0.42	Galvanised	FNE11600	0	0	0	2
Bluescope	0.55	PVDF	FNE11606	0	0	0	1
Pacific Coil Coaters	0.42	MagnaFlow®	19-002186	0	0	0	3

### CONCLUSION

Stramit® products made from these steel sources and with the tested finishes would be considered non-combustible according to NCC 2019 Volume One Part C1.9(e) and Volume Two Part 3.7.1.1.

**It is important to note that Stramit® sheeting is only one component used in construction of these building elements, and other components must also meet the necessary requirements to satisfy the criteria.**

For information on performance of residences in a bushfire situation, please refer to the bulletin based on the [NASH Bushfire Standard](#) on the Bluescope® website.

The information contained within this brochure is intended for general use and information only. Before application in a particular situation, Stramit recommends that you obtain appropriate independent qualified expert advice confirming the suitability of product(s) and information in question for the application proposed. While Stramit accepts its legal obligations, be aware however that to the extent permitted by law, Stramit disclaims all liability (including liability for negligence) for all loss and damage resulting from the direct or indirect use, or reliance on, the information provided in this brochure.

TM & ® are Trademarks of Stramit Corporation Pty Limited ABN 57 005 010 195 trading as Stramit Building Products. COLORBOND® and ZINCALUME® are registered trademarks of BlueScope Steel Limited. © Stramit Corporation Pty Limited. STR035-OCT21.